

PRODUCT SHEET:

RAMPMATIC™ GSE RIB AND MUD & SNOW



The most reliable GSE tires on the market to get the job done!



RIB 6.00X9, 10 PLY WITH INNER TUBE AND FLAP

RIB 8.00X16.5, 10 PLY

TIRES THAT NEVER NEED TO TREAD LIGHTLY

Whether it's blistering hot, snow is sticking, or the rain is relentless, it is more important than ever for GSE vehicles to perform at optimal efficiency.

Designed to handle the high heat, the freezing cold, and on the roughest ramp surfaces, the **Rampmatic™** tires from **Sage Parts** provide maximum traction in all ramp and weather conditions.



RIB TREAD



M+S TREAD

Available with Rib or M+S tread, **Rampmatic™** tires are made of a specially designed rubber compound that is built to last and produces the lowest cost per engine hours on even the harshest ramp conditions.

FEATURES

- ✓ MAXIMUM TRACTION IN ALL SURFACE CONDITIONS
- ✓ BUILT TO OUT PERFORM OTHER BRANDS
- ✓ BETTER PERFORMANCE MEANS BETTER FUEL ECONOMY
- ✓ SPECIALLY DESIGNED WITH SPECIAL RIM GUARD PROTECTION FOR ENHANCED SIDEWALL LIFE
- ✓ INCREASED TREAD DEPTH FOR LONGER LIFE
- ✓ SMOOTHER OVERALL RIDE

SAGE PARTS

Anticipating needs, meeting demands. Reducing costs.



Sage Parts

30 Hub Drive, Melville, NY 11747

+1.877.SAGE.877 | +1.631.501.1300 Tel

+1.631.501.1619 Fax | info@sageparts.com

www.sageparts.com

PRODUCT SHEET:

TIRE SIZES AND SPECIFICATIONS



RIB 6.00X9 10 PLY WITH
INNER TUBE AND FLAP

AVAILABLE SIZES

SAGE PART NUMBER	TYPE	RIM WIDTH	INFLATED DIMENSIONS +/-2%		NSD		PLY RATING	INFLATION PRESSURE		LOAD CAPACITY
			OUTER DIAMETER	SECTION WIDTH	mm	(32 nd of an inch)		bar	psi	
SPR600X9	TT	4.00 in	21.50 in	6.81 in	16.50	20/32	10	8.6	125	2,825 lbs (1,280 kg)
SPR650X10	TT	5.00 in	23.62 in	7.56 in	16.50	20/32	12	9.65	140	2,850 lbs (1,290 kg)
SPR800X165	TL	6.00 in	29.13 in	8.40 in	14.00	19/32	8	4.48	65	3,100 lbs (925 kg)
SPR875X165	TL	6.75 in	30.12 in	9.05 in	17.50	22/32	10	5.52	80	3,100 lbs (1,410 kg)
SPT875X165MS*	TL	6.75 in	30.12 in	9.05 in	18.50	23/32	10	5.52	80	2,700 lbs (1,410 kg)
SPR165X13	TL	4.50 in	23.23 in	6.42 in	16.50	20/32	10	4.48	65	2,325 lbs (1,050 kg)
SPR700X15	TT	6.00 in	29.72 in	7.80 in	17.50	22/32	12	5.17	75	3,300 lbs (1,500 kg)

*Mud & Snow Tread

TT — Tub and flap included



SAGE PARTS

Anticipating needs, meeting demands. Reducing costs.



Sage Parts

30 Hub Drive, Melville, NY 11747

+1.877.SAGE.877 | +1.631.501.1300 Tel

+1.631.501.1619 Fax | info@sageparts.com

www.sageparts.com